

Q. When does my Saab need an engine oil change?				A. Every 5000 miles or once a year, whichever comes first.				
Q. What kind of oil do I use and how much does it take for my model?				A. Scroll through the chart below to find the recommended oil (highlighted) and quantity for your model.				
Q. What do I need to change my oil?				A. Use the chart below to find all your parts for your model.				
Model	Year	Engine	Recommended Oil Type	Recommended Viscosity	Oil Quantity	Oil Filter	Associated Parts	Service Interval
Classic 900	1979-1993 incl. 1994 Convertible	B201, B202, B212	Conventional, Semi or Full Synthetic 10W- 30	API SJ, CCMC G4/G5, SAE 10W-30 , 10W-40, 5W-30, 5W-40, 15W-40 may be used except in cold weather	4.5Qts	93186554	9132929 Drain Plug	Every 5000 miles or once a year, whichever comes first.
							9132937 Gasket-Oil Drain plug	
9000	1986-1989	B202	Conventional, Semi or Full Synthetic 10W- 30	API SJ, CCMC G4/G5, SAE 10W-30 , 10W-40, 5W-30, 5W-40, 15W-40 may be used except in cold weather	4.5Qts	93186554	7563042 Drain Plug	Every 5000 miles or once a year, whichever comes first.
							7522709 Gasket-Oil Drain Plug	
9000CS	1990-1998	B234, B308i	Full Synthetic 10W-30	API SJ, CCMC G4/G5, SAE 10W-30 , 10W-40, 5W-30, 5W-40, 15W-40 may be used except in cold weather. For areas with temp above 60°F 15W-50 or 20W-50 may be used.	4Cyl 4.2Qts	4-Cyl 93186554	7563042 Drain Plug	Every 5000 miles or once a year, whichever comes first.
					6Cyl 4.7Qts		6-Cyl 93178952	
							90409376 Drain Plug	
							11016282 Gasket-Oil Drain plug	

NG 900	1994-1998	B204, B234, B258	Full Synthetic 10W-30	API SJ, CCMC G4/G5, SAE 10W-30 , 10W-40, 5W-30, 5W-40, 15W-40 may be used except in cold weather. For areas with temp above 60°F 15W-50 or 20W-50 may be used.	4Cyl 4.2Qts	4-Cyl 93186554	9132929 Drain Plug	Every 5000 miles or once a year, whichever comes first.
					6Cyl 4.7Qts		6-Cyl 93178952	
6Cyl 4.7Qts	6-Cyl 93178952	90409376 Drain Plug						
		6Cyl 4.7Qts	6-Cyl 93178952	11016282 Gasket-Oil Drain plug				
9-3	1999-2002 incl 2003 Convertible			B204, B205, B235	Full Synthetic 0W-40	API SJ, CCMC G4/G5, SAE 5W- 30, 0W-30, 5W-40, ILSAC GF- 3 specification is approved for use in applicable markets. Oils with viscosity's 0W- 40 /0W-50 of well-known brands and fulfilling minimum ACEA A3/B3 are also recommended, especially for extreme driving conditions.	4.2Qts	4-Cyl 93186554
		9132937 Gasket-Oil Drain plug						
9-5	1999-2009	B235, B308t	Full Synthetic 0W-40	API SM or higher, GM-LL-A- 025, ACEA A3/B3, SAE 0W-30, 0W-40, 5W-30 or 0W-40	4Cyl 4.2Qts	93186554 ALL Engines	9132929 Drain Plug	Every 5000 miles or once a year, whichever comes first.
					6Cyl 4.6Qts		9132937 Gasket-Oil Drain plug	

9-3 SS	2003-2011	B207, B284	Full Synthetic 0W-40	API SM or higher, GM-LL-A-025, ACEA A3/B3, SAE 0W-30, 0W-40, 5W-30 or 0W-40	4Cyl 6.3Qts	4Cyl 12605566	11562588 Drain Plug	Every 5000 miles or once a year, whichever comes first.	
					6Cyl 6.0Qts		6Cyl 93186310		3536966 Gasket-Oil Drain plug
									12580255 Oil Filter Housing O-ring
						9132929 Drain Plug			
					12616850 Gasket-Oil Drain plug				
					12577653 Oil Filter O-ring included with Filter 93186310				
9-2X	2005-2006	EJ205, EJ253, EJ255	Full Synthetic 5W-30	API SM, ILSAC GF-4 or higher SAE 5W-30 For areas with very high temperatures or used for heavy-duty applications SAE 30, 40, 10W- 50, 20W-40, 20W-50 are recommended	4.2Qts	32009814	32008482 Drain Plug	Every 5000 miles or once a year, whichever comes first.	
						32005452 Gasket-Oil Drain plug			
9-7X	2005-2009	LL8 = 4.2L Inline 6 LH6 = 5.3L V8, LS2 = 6.0L V8	Full Synthetic 5W-30	LL8/LH6/LS2 - Mobil 1 Synthetic 5W-30	LL8 6Cyl 7Qts	LL8 6Cyl 19210285	11562588 Drain Plug	Every 5000 miles or once a year, whichever comes first.	
					LH6/LS2 V8 6Qts		LH6/LS2 V8 19303975		Drain Plug Gasket comes with drain plug
						11562588 Drain Plug			
					Drain Plug Gasket comes with drain plug				

NG 9-5	2010-2011	A20NHT 4 Cyl	Full Synthetic 5W-30 Annual Protection dexos® 2	dexos1™ Gen 2 GM4718M ACEA A3/B4 API SN SAE 5W-30 , 5W-40, 0W-30 or 0W-40	4Cyl 6.3Qts	4Cyl 12605566	11562588 Drain Plug	Every 5000 miles or once a year, whichever comes first.
		A28NER V6			6Cyl 6.6Qts		6 Cyl 93186310	
11562588 Drain Plug	12577653 Oil Filter O-ring included with Filter 93186310							
12616850 Gasket-Oil Drain plug								
9-4X	2011	A28NER 2.8 V6T	Full Synthetic 5W-30 Annual Protection dexos® 2	dexos1™ Gen 2 GM4718M ACEA A3/B4 API SN SAE 5W-30 , 5W-40, 0W-30 or 0W-40	A28NER 6Qts	A28NER 93186310	11562588 Drain Plug	Every 5000 miles or once a year, whichever comes first.
							12577653 Oil Filter O-ring included with Filter 93186310	
		A30YH 3.0 V6i			A30YH 6Qts	A30YH 89017525	12616850 Gasket-Oil Drain plug	
							11562588 Drain Plug	